



电线颜色标志:
 RED 红色
 BLU 蓝色
 BRN 棕色
 YEL 黄色
 GRN/YEL 黄绿色

Cossiga
 BTGOR12 E00128
 P93-056 220V~240V, 50/60Hz, 1P

English	中文
Hair hotline terminal	发热线端子
winding protector	绕组保护
starting winding	启动绕组
main winding	主线绕组
Relay / copacitor	继电器 / 电容
Plug	插头
Digital Controller	数字控制器
Sensor	感温探头
Contact	接触器
Compressor	压缩机
Condensing Fan	冷凝风扇
Convection Fan	对流风扇
LED Light	LED 灯条
LED DRIVER	LED 控制装置
Vent Fan	散热风扇
EMI FILTER	EMI 滤波器

A-4	更改LED电源零线输入位置	肖辉绪	2017-11-17
A-2	增加一条LED (S21-293)	林明亮	20170614
A-1	增加门边发热线 (S16-816)	林明亮	2017-05-03
REV	DESCRIPTION OF REVISIONS	BY	APP
L1/L1	ECO		DATE
Hole	0~3.2 < 3.2 ~ 6.35 < 6.35 ~ 12.7 < 12.7 ~ 19.05 < 19.05 ~ 25.4	+0.127	+0.152
Tolerance	-0.05	-0.05	-0.05
Linear	0.5~6	< 6 ~ 30	< 30 ~ 120
Tolerance	±0.3	±0.5	±0.8

DO NOT SCALE THIS DRAWING
 CRITICAL DIMENSION
 OTHER DIMENSIONS ARE IN mm UNLESS SPECIFIED
 1. DIMENSIONS ARE IN mm UNLESS SPECIFIED
 2. SHEET METAL FLAT PATTERN ±3.
CTQ SYMBOL
 MEASURABLE ATTRIBUTES THAT ARE CRITICAL TO CUSTOMER SATISFACTION THIS INCLUDES PART IS NOT LIMITED TO FIT, FORM, FUNCTION AND APPEARANCE
 CPK OF 1.33 OR GREATER AS DEFINED BY INSPECTION STANDARD

COSSIGA Foshan Cossiga Trading Ltd. 佛山科西加贸易有限公司

THIS PRINT REMAINS THE PROPERTY OF COSSIGA LTD. ALL INFORMATION CONTAINED HEREON IS CONFIDENTIAL. IT IS LOANED, SUBJECT TO RETURN UPON DEMAND, AND ON THE EXPRESS CONDITION THAT IT IS NOT TO BE COPIED OR USED DIRECTLY OR INDIRECTLY IN ANY MANNER THAT IS DETRIMENTAL TO OUR INTERESTS.

DESCRIPTION: BTGOR12
 DWG NO.: E00128
 DRAWN BY: DATE: VER: A-4
 APPROVED: DATE: DWG TITLE: 电路图
 WEIGHT: 1
 SCALE: A4
 SHEET 1 OF 1