



电线颜色标志:
 白色
 红色
 蓝色
 棕色
 黄色
 黄绿色

| | |
|----------------------------------|----------------|
| English | 中文 |
| Plug | 插头 |
| Power switch (Indicator lamp) | 电源开关 (带指示灯) |
| Digital Controller | 数字控制器 |
| Sensor | 感温探头 |
| Contactor | 接触器 |
| Heater | 加热器 |
| Convection Fan | 对流风扇 |
| Light switch (Indicator lamp) | 照明开关 (带指示灯) |
| LED Light | LED 灯条 |
| LED DRIVER | LED 控制装置 |
| Vent Fan | 散热风扇 |
| EMI FILTER | EMI 滤波器 |
| Thermal Protector | 热保护器 |

| | | | | | |
|-----------|--|-----------------|---------|----------|------------------|
| A-5 | 更改S16-876数字温控器、更改 N 接线位置 探头接线位置 | | | | |
| A-4 | 更改散热风扇的接线方式 | 肖燊绪 | | | |
| A-3 | 增加STGH12机型, 原机型 C4HT12/SC4HT12取消一个S01-058 | 林明亮 | | | 2017/07/31 |
| A-2 | 增加2个热保护器 | 李海斌 | | | 2016/11/08 |
| REV | DESCRIPTION OF REVISIONS | ECO | BY | APP | DATE |
| LVL | | | | | |
| Hole | 0~3.2<3.2~6.35<6.35~12.7<12.7~19.05<19.05~25.4 | +0.152 | -0.05 | +0.254 | Angle ±2° |
| Tolerance | -0.1 -0.05 | -0.127 -0.05 | -0.05 | -0.05 | Tolerance ±2° |
| Linear | 0.5~6 | <6~30 | <30~120 | <120~400 | <400~1000 |
| Tolerance | ±0.3 | ±0.5 | ±0.8 | ±1.2 | ±2 |

DO NOT SCALE THIS DRAWING
 CRITICAL DIMENSION
 DIMENSIONS ARE IN mm UNLESS OTHERWISE NOTED
 2. SHEET/DRAWING FLAT PATTERN=±3.
C710 SYMBOL
 MEASURABLE ATTRIBUTES THAT ARE CRITICAL TO CUSTOMER SATISFACTION, THIS INCLUDES BUT IS NOT LIMITED TO FIT, FORM, FUNCTION, AND APPEARANCE
 C710 OF 1.33 OR GREATER AS DEFINED BY INSPECTION STANDARD

Cossiga E000031
 C4HT12/SC4HT12/STGH12
 P90-716/P92-381/P93-042, 240V, 50Hz 1P

COSSIGA Foshan Cossiga Trading Ltd. 佛山科西加贸易有限公司

THIS PRINT REMAINS THE PROPERTY OF COSSIGA LTD. ALL INFORMATION CONTAINED THEREON IS CONFIDENTIAL. IT IS LOANED, SUBJECT TO RETURN UPON DEMAND, AND ON THE EXPRESS CONDITION THAT IT IS NOT TO BE COPIED OR USED DIRECTLY OR INDIRECTLY IN ANY MANNER WHICH IS DETRIMENTAL TO OUR INTERESTS.

DESCRIPTION: C4HT12/SC4HT12/STGH12
 Dwg Title: 电路图
 Dwg No: E00031
 Ver: A-5
 Date: DATE
 Appr: APPROVED: DATE: DATE

QTY: 1
 SIZE: A4
 SHEET 1 OF 1