



电线颜色标志:  
 WHI 白色  
 RED 红色  
 BLU 蓝色  
 BLA 黑色  
 BRN 棕色  
 GRN/YEL 黄绿色

English	中文
Plug	插头
Power switch (Indicator lamp)	电源开关 (带指示灯)
Digital Controller	数字控制器
Sensor	感温探头
Contactor	接触器
Heater	加热器
Convection Fan	对流风扇
Light switch (Indicator lamp)	照明开关 (带指示灯)
LED Light	LED 灯条
LED DRIVER	LED 控制装置
Vent Fan	散热风扇
EMI FILTER	EMI 滤波器
Thermal Protector	热保护器

A-3	更改S16-876数字温控器、更改L 接线位置 探头接线位置。								
A-2	更改散热风扇的接线方式								
A-1	取消-A-S01-058								
REV	DESCRIPTION OF REVISIONS	ECO	BY	APP	DATE				
LVL									
Hole	0~3.2	3.2~6.35	6.35~12.7	12.7~19.05	19.05~25.4	Angle			
Tolerance	+0.1	+0.127	+0.152	+0.2	+0.254	Tolerance			
Linear	0.5~6	<6~30	<30~120	<120~400	<400~1000	<1000~2000			
Tolerance	±0.3	±0.5	±0.8	±1.2	±2	±3			

DO NOT SCALE THIS DRAWING

CRITICAL DIMENSION

OTHERWISE NOTED

1. DIMENSIONS ARE IN mm UNLESS SHEET/FLAT PATTERN=±3.

**C710 SYMBOL**

MEASURABLE ATTRIBUTES THAT ARE CRITICAL TO CUSTOMER SATISFACTION. THIS INCLUDES BUT IS NOT LIMITED TO FIT, FORM, FUNCTION, AND APPEARANCE

CW OF 1.33 OR GREATER AS DEFINED BY INSPECTION STANDARD

**COSSIGA**

Foshan Cossiga Trading Ltd.

佛山科西加贸易有限公司

THIRD ANGLE

DESCRIPTION: D4HH15/SD4HH15/BRIGHT15 电路图

DWG NO: E00046

VER: A-3

DATE: DATE: DATE: DATE:

SCALE: SCALE: SCALE: SCALE:

QTY: 1

SIZE: A4

SHEET 1 OF 1

Cossiga  
 D4HH15/BRIGHT15 E00046  
 F93-006/F93-011, 240V,  
 50Hz 1P

LED Light S21-559 LED Light S21-559 LED Light S21-559 LED Light S21-559