



电线颜色标志:  
 RED 红色  
 BLU 蓝色  
 BRN 棕色  
 YEL 黄色  
 GRV/YEL 黄绿色

English	中文
Hair hotline	发热线
winding protector	绕组保护
starting winding	启动绕组
main winding	主线绕组
Relay / copacitor	继电器 / 电容
Transformer	变压器
Glasses	玻璃
Plug	插头
Digital Controller	数字控制器
Sensor	感温探头
Contactoer	接触器
Compressor	压缩机
Condensing Fan	冷凝风扇
Convection Fan	对流风扇
LED Light	LED 灯
LED DRIVER	LED 控制装置
Heat	单头发热管

B-1	将开关电源更换为RS-7S-12	EC019-019	邓伟雄	2019. 11. 25	
B-1	取消交流接触器	EC019-022	邓伟雄	2019. 11. 25	
B-0	更改LED电源零线输入位置		肖解绪	2017-11-16	
A-5	更换S16-843数字温控器, 增加S16-870电源开关及S16-871灯开关		林明亮	2017-08-08	
A-4	更改发热玻璃变压器由原来S21-556改为S16-856		林明亮	2017-07-04	
A-3	更改PTC发热管通电模式: 由压缩机同步启动改成发热风机同步		林明亮	2017-06-12	
REV	DISCRIPTION OF REVISIONS	ECO	BY	APP	DATE
LVL					
Hole	0~3.2<3.2~6.35<6.35~12.7<12.7~19.05<19.05~25.4	+0.127 -0.05	+0.2 -0.05	+0.254 -0.05	Angle ±2°
Tolerance					±2
Linear	0.5~6	<6~30	<30~120	<120~400	<400~1000
Tolerance		±0.3	±0.5	±1.2	±2

Cossiga  
 STR99 E00110  
 P93-031, 220V-240V, 50/60Hz, 1P

DO NOT SCALE THIS DRAWING

CRITICAL DIMENSION

OTHERWISE NOTED

2. SHEET METAL FLAT PATTERN=±3.

**CTIQ SYMBOL**

MEASURABLE ATTRIBUTES THAT ARE CRITICAL TO CUSTOMER SATISFACTION. THIS INCLUDES BUT IS NOT LIMITED TO FIT, FORM, FUNCTION, AND APPEARANCE

CW OF 1.33 OR GREATER AS DEFINED BY INSPECTION STANDARD

**COSSIGA**

Foshan Cossiga Trading Ltd.

佛山科西加贸易有限公司

THIRD ANGLE

DESCRIPTION: 电路图

DWG NO: STGRF9

VER: B-1

DATE: DATE

SCALE: SCALE

QTY: 1

SIZE: A4

SHEET 1 OF 1