



电线颜色标志:  
 RED 红色  
 BLU 蓝色  
 BRN 棕色  
 YEL 黄色  
 GRN/YEL 黄绿色

English	中文
Hair hotline	发热线
terminal	端子
winding protector	绕组保护
starting winding	启动绕组
main winding	主线绕组
Relay / copacitor	继电器 / 电容
Transformer	变压器
Glasses	玻璃
Plug	插头
Digital Controller	数字控制器
Sensor	感温探头
Contact	接触器
Compressor	压缩机
Condensing Fan	冷凝风扇
Convection Fan	对流风扇
LED Light	LED 灯
LED DRIVER	LED 控制装置
Heat	单头发热管

B-1	将开关电源更换为RS-7512	EC019-019	邓伟雄	2019.11.25		
B-1	取消交流接触器	EC019-022	邓伟雄	2019.11.25		
B-0	更改LED电源等级输入位置		肖辉绪	2017-11-16		
A-5	更换S16-843数字温控器、增加S16-870电源开关及S16-871开关		林明亮	2017-08-08		
A-4	更改发热玻璃变压器由原来S21-556改用S16-856		林明亮	2017-07-04		
A-3	更改PTC发热管通电模式: 由压缩机同步启动改成蒸发器风机同步		林明亮	2017-06-12		
REV	DESCRIPTION OF REVISIONS	ECO	BY	APP	DATE	
LVL						
Hole	0~3.2<3.2~6.35<6.35~12.7<12.7~19.05<19.05~25.4	+0.127	-0.152	+0.2	-0.254	Angle ±2°
Tolerance	-0.05	-0.05	-0.05	-0.05	-0.05	Tolerance ±2
Linear	0.5~6	<6~30	<30~120	<120~400	<400~1000	<1000~2000
Tolerance	±0.3	±0.5	±0.8	±1.2	±2	±3

DO NOT SCALE THIS DRAWING.  
 CRITICAL DIMENSIONS ARE IN mm UNLESS OTHERWISE NOTED.  
 1. DIMENSIONS ARE IN mm UNLESS OTHERWISE NOTED.  
 2. SHEET/FLAT PATTERN=±3.  
**C170 SYMBOL**  
 MEASURABLE ATTRIBUTES THAT ARE CRITICAL TO CUSTOMER SATISFACTION, THIS INCLUDES BUT IS NOT LIMITED TO FIT, FORM, FUNCTION, AND APPEARANCE.  
 CW OF 1.33 OR GREATER AS DEFINED BY INSPECTION STANDARD

**COSSIGA**  
 Foshan Cossiga Trading Ltd.  
 佛山科西加贸易有限公司

THIS PRINT REMAINS THE PROPERTY OF COSSIGA LTD. ALL INFORMATION CONTAINED THEREON IS CONFIDENTIAL. IT IS LOANED, SUBJECT TO RETURN UPON DEMAND, AND ON THE EXPRESS CONDITION THAT IT IS NOT TO BE COPIED OR USED DIRECTLY OR INDIRECTLY IN ANY MANNER WHICH IS DETRIMENTAL TO OUR INTERESTS.

DESCRIPTION: STGRF12  
 DWG TITLE: 电路图  
 DWG NO: E00111  
 VER: B-1  
 DATE: DATE: DATE: DATE:  
 APPROVED: DATE: DATE: DATE: DATE:  
 MATERIAL: MATERIAL:  
 QTY: 1  
 WEIGHT: WEIGHT:  
 SCALE: SCALE:  
 SIZE: A4  
 SHEET 1 OF 1

Cossiga  
 STGRF-12 E00111  
 F93-032, 220V-240V, 50/60Hz 1P