# cossiga


## BTGOR6





#### **PRODUCT FEATURES**


- Open front
- Stainless steel hinged rear door
- Deck forced refrigeration
- Double glazed glass ends
- Two adjustable glass shelves
- Flat or angled shelves
- Ticket strips on shelves and base
- Under shelf and canopy LED lights
- Integral condenser
- Pull down night blind
- Perspex riser

Maximum shelf load weight 15kg spread evenly Adjustable rear or front venting









#### **CABINET DIMENSIONS & SPECIFICATIONS**

Prior to installation see, installation guidelines and ventilation requirements document

MODEL	CABINET					OPERATING TEMP	SHELF	BASE TRAY	TOTAL FOOD	DISPLAY M <sup>2</sup>	INTERNAL VOLUME M <sup>3</sup>	FREQUENCY	REFRIGERANT	POWER		CONNECTION ELECTRICAL POWER CORD 2200MM		VOLTAGE	PACKED FOR SHIPPING			
	LENGTH [MM]	DEPTH [MM]	HEIGHT [MM]	WEIGHT KG		DEG C	WXD	WXD	100MM UNITS					KW 230V	AMP	NZ/AUS 10 AMP	UK 13 AMP		LENGTH [MM]	DEPTH [MM]	HEIGHT [MM]	WEIGHT
BTGOR6	600	750	1380	175	2 + BASE	3-5	490 X 440	545 x 515	55	0.60	0.29	50/60 HZ	R290	1.10	6.0	3 PIN PLUG	3 PIN PLUG	220- 240V	700	830	1550	180





# BTGOR9 free-standing multideck open front refrigerated

## cossiga


#### BTGOR9





#### **PRODUCT FEATURES**


- Open front
- Stainless steel hinged rear doors
- Deck forced refrigeration
- Double glazed glass ends
- Two adjustable glass shelves
- Flat or angled shelves
- Ticket strips on shelves and base
- Under shelf and canopy LED lights
- Integral condenser
- Pull down night blind
- Perspex riser

Maximum shelf load weight 15kg spread evenly Adjustable rear or front venting









#### **CABINET DIMENSIONS & SPECIFICATIONS**

Prior to installation see, installation guidelines and ventilation requirements document

MODEL	CABINET			CABINET		OPERATING TEMP	S SHELF BASE TRAY		TOTAL FOOD	DISPLAY M <sup>2</sup>	INTERNAL VOLUME M <sup>3</sup>	FREQUENCY	REFRIGERANT	REFRIGERANT POWER		CONNECTION ELECTRICAL POWER CORD 2200MM		VOLTAGE	1	PACKED FOR SHIPPING		G
	LENGTH [MM]	DEPTH [MM]	HEIGHT [MM]											KW 230V		NZ/AUS 10 AMP			LENGTH [MM]	DEPTH [MM]	HEIGHT [MM]	WEIGHT
BTGOR9	900	750	1380	224	2 + BASE	3-5	790 X 440	845 x 515	114	0.96	0.45	50/60 HZ	R290	1.10	6	3 PIN PLUG	3 PIN PLUG	220- 240V	1000	830	1550	235








#### BTGOR12





#### **PRODUCT FEATURES**


- Open front
- Stainless steel hinged rear doors
- Deck forced refrigeration
- Double glazed glass ends
- Two adjustable glass shelves
- Flat or angled shelves
- Ticket strips on shelves and base
- Under shelf and canopy LED lights
- Integral condenser
- Pull down night blind
- Perspex riser

Maximum shelf load weight 15kg spread evenly Adjustable rear or front venting









## **CABINET DIMENSIONS & SPECIFICATIONS**

Prior to installation see, installation guidelines and ventilation requirements document

																	0					
MODEL	CABINET			CABINET		OPERATING TEMP	SHELF	BASE TRAY	TOTAL FOOD	DISPLAY M <sup>2</sup>	INTERNAL VOLUME M <sup>3</sup>	FREQUENCY	REFRIGERANT POWER		WER	CONNECTION ELECTRICAL POWER CORD 2200MM		VOLTAGE	PACKED FOR SHIPPING			
	LENGTH [MM]	DEPTH [MM]	HEIGHT [MM]											KW 230V		NZ/AUS 10 AMP			LENGTH [MM]	DEPTH [MM]	HEIGHT [MM]	WEIGHT
BTGOR12	1200	750	1380	273	2 + BASE	3-5	1085 X 440	1145 x 515	123	1.31	0.60	50/60 HZ	R290	1.39	7.6	3 PIN PLUG	3 PIN PLUG	220- 240V	1300	830	1550	279



