







## CM

LSCM2  
LSCM3  
LSCM4  
LSCM5  
LSCM6

- Ceramic Heated Glass
- Overhead Halogen Lamps with adjustable dimmer
- Digital thermostatic controller
- Heat indicating LED lights




## CABINET DIMENSIONS & SPECIFICATIONS

MODEL	CABINET			WEIGHT KG	BENCH TOP CUT OUT HOLE SIZE	TEMP RANGE DEG C	DISPLAY AREA M2	FREQUENCY	OPERATING CURRENT WITH LAMPS AMPS	OPERATING CURRENT NO LAMPS AMPS	POWER WITH LAMPS KW 230V	CONNECTION ELECTRICAL POWER CORD 3000MM NZ/AUS/UK	VOLTAGE	PACKED FOR SHIPPING			
	LENGTH [MM]	DEPTH [MM]	HEIGHT [MM]											LENGTH [MM]	DEPTH [MM]	HEIGHT [MM]	WEIGHT [KG]
LSCM2	805	690	555	65	775x672	75-95	0.33	50/60 HZ	7.9	5.2	1.9	15 AMP LEAD ONLY	220-240V	910	770	410	76
LSCM3	1145	690	555	65	1115x672	75-95	0.51	50/60 HZ	11.7	7.61	2.691	15 AMP LEAD ONLY	220-240V	1250	770	410	88
LSCM4	1485	690	555	85	1455x672	75-95	0.68	50/60 HZ	15.7	10.25	3.611	20 AMP LEAD ONLY	220-240V	1590	770	410	107
LSCM5	1825	690	555	97	1795x672	75-95	0.86	50/60 HZ	19.6	12.78	4.508	20 AMP LEAD ONLY	220-240V	1930	770	410	128
LSCM6	2165	690	555	109	2135x672	75-95	1.04	50/60 HZ	23.5	15.32	5.405	30 AMP LEAD ONLY	220-240V	2270	770	410	140
LSSC1	570	365	1.5	18	545 x 338	75-95		50/60 HZ		2.52	0.579	10 AMP 3 PIN PLUG	220-240V	680	420	165	20



## CM<sup>LSSC1</sup>






- Single ceramic heated glass
- Digital thermostatic controller
- Heat indicating LED lights on panel
- Flush mount drop in module



## ELECTRICAL POWER

Electrical power cord 3000mm  
1 phase connection required.

Unit can be hard wired to isolation switch or fitted with suitable heavy duty plug such as PDL 56 series or Commando style plug.



Panel  
Controllers  
LSCM 2/3 X 1  
LSCM 4/5/6 X 2

## PANEL CONTROLLERS


MODEL	NUMBER OF PANELS	NUMBER OF CONTROLLERS	GROUP OF PANELS CONTROLLED
LSCM2	2	1	CONTROLLER 1 - 2
LSCM3	3	1	CONTROLLER 1 - 3
LSCM4	4	2	CONTROLLER 1 - 2 CONTROLLER 2 - 2
LSCM5	5	2	CONTROLLER 1 - 2 CONTROLLER 2 - 3
LSCM6	6	2	CONTROLLER 1 - 3 CONTROLLER 2 - 3

## GLASS CANOPY OPTIONS


ASSEMBLY REQUIRED




GLFT Flat Top




GLFS Full Square Glass




## FLUSH BENCH TOP DETAIL





Additional support may be required under bench ie. stainless steel hollow section to frame






Counter top joinery must be of sufficient structural capacity to take the weight of the LS unit when the flange detail has been made.










Drop into base




LS HEATED CERAMIC RISER	
MODEL	CODE
LSCM3 RISER	F93-197
LSCM4 RISER	F93-198
LSCM5 RISER	F93-199
LSCM6 RISER	F93-200



Stainless Steel Construction  
Fits all LSCM units  
Intergrated Digital Controller  
Adjustable feet



## SILICONE ELEMENT REPLACEMENT



The element is accessible through the base of the unit. Ensure to leave space to allow access for service on the under side of the unit. If no access is achievable the unit will need to be lifted out.



## Locations to avoid

- Drafts from doorways
- Airflow from air-conditioning ducts
- Hot air from motors i.e. refrigerators
- Direct sunlight

## Disrupted air flow

Heat from other equipment and natural conditions, such as direct sunlight straight on units, can cause cooling to fail and overload compressor

Mechanical air flows, such as diffusers and fans can disturb the air curtain on units causing failure